

ITT

BCELEACC

Residential Water Systems

CentriPro ELECTRICAL ACCESSORIES

- Replacement Motor Leads
- Cable Accessories
- Lightning Protection Devices
- Bulk Cable
- Packaged Cable

FEATURES

■ Motor Leads:

- 4" CentriPro Motor Leads
- 6" CentriPro Motor Leads
- 4" Franklin Electric Motor Leads

■ Cable Accessories:

- Heat Shrink Kits

■ Lightning Protection Devices:

- AW24-1 & AW24-3 Lightning Arrestors
- Watt-Knot® Voltage Surge Arrestors

■ Bulk cable with ground.

- Twisted design, solid copper conductor.
- PVC insulated.
- AWG 8-14

■ Packaged Cable for 4" CentriPro and F.E. Motors


- No splice required, connector threads into motor.
- 2 and 3 wire with ground
- Lengths from 50' to 300'.
- Twisted design stranded wire.



CentriPro is a brand of ITT Corporation.

www.centripro.com

Engineered for life



ITT

CENTRIPRO Residential Water Systems

4" CENTRIPRO MOTOR LEADS

Order No.	Description
AW348C	3 wire 48" with ground and (2) screws
AW3100C	3 wire 100" with ground and (2) screws
AW248C	2 wire 48" with ground and (2) screws
AW2100C	2 wire 100" with ground and (2) screws

6" CENTRIPRO MOTOR LEADS

Order No.	Description	Used On
CPML-12	150", 12 / 4	5-15HP 1Ø; 5 - 25 & 40hp, 3Ø
CPML-10	150", 10 / 4	30 & 50HP, 3Ø
CPML-8	150", 8 / 4	Optional for 30-50HP, 3Ø

4" FRANKLIN ELECTRIC MOTOR LEADS



Order No.	Description
AW248	2 wire, 48" with ground
AW2100	2 wire, 100" with ground
AW283	3 wire, 48" double ended lead

Packaged Cable for 4" Submersible Motors – No Splice Required

FOR CENTRIPRO 4" MOTORS

Length in Feet	3-wire Order No.	2-wire Order No.
50	ACPC3050	ACPC2050
100	ACPC3100	ACPC2100
150	ACPC3150	ACPC2150
200	ACPC3200	ACPC2200
250	ACPC3250	ACPC2250
300	ACPC3300	ACPC2300

- AWG 12, stranded copper, twisted design with ground.
- XLPE - suitable for potable water.
- No underwater splice required.
- CentriPro motor connector attached.




FOR FRANKLIN ELECTRIC 4" MOTORS

Length in Feet	3-wire Order No.	2-wire Order No.
60	AWPC3060	AWPC2060
100	AWPC3100	AWPC2100
150	AWPC3150	AWPC2150
200	AWPC3200	AWPC2200
250	AWPC3250	AWPC2250
300	AWPC3300	AWPC2300

- AWG 12, stranded copper, twisted design with ground
- Santoprene® thermoplastic rubber insulated.
- F.E. Motor connector attached.

NOTE: Packaged Cable for FE motors will be discontinued when In Stock units are all sold.



ITT

CENTRIPRO Residential Water Systems

Bulk Cable with Ground

AWP15

- Reel lengths 500' or 1000', 2 or 3 wire with ground.
- UL listed, NEC standard.
- PVC insulated, 600 V, 60°C.
- Twisted design.
- Solid copper conductor sizes 14, 12, 10, 8.

BULK CABLE

B

PVC insulation with ground

Order No.	Size No.	Length
AWP15-145	14 3-wire	500 ft.
AWP15-141		1000 ft.
AWP152-145	14 2-wire	500 ft.
AWP152-141		1000 ft.
AWP15-125	12 3-wire	500 ft.
AWP15-121		1000 ft.
AWP152-125	12 2-wire	500 ft.
AWP152-121		1000 ft.
AWP15-105	10 3-wire	500 ft.
AWP15-101		1000 ft.
AWP152-105	10 2-wire	500 ft.
AWP152-101		1000 ft.
AWP15-85	8 3-wire	500 ft.
AWP15-81		1000 ft.

Sold only in reels.

LIGHTNING PROTECTION




Order No.	Description
AW24-1	Single phase lightning/surge arrester, 0-125 volts to ground
AW24-3	Three phase lightning/surge arrester, 0-125 volts to ground
1040175	Watt Knot voltage/surge arrester, 230 V, 1Ø for ½ – 15 HP motors
1040185	Watt Knot voltage/surge arrester, 230/460 V, 3Ø for 1.5 – 200 HP motors

HEAT SHRINK TYPE WIRE SPLICE KITS



Order No.	Shrink Tubes	Butt Connectors	Use on
AW25-3	4	(4) # 8	#8 - #12 Wire
AW25-4	4	(4) # 10 - #12	#10 - #14 Wire
AW25-5	3	(3) #10 - #12	#10 - #14 Wire
AW25-6	3 Large & 3 Small	None	#6 - #14

Use for making waterproof connections on submersible cable.
Mandatory for use on underwater splices where variable speed drives are used.



ITT

Residential Water Systems



CentriPro and the ITT Engineered Blocks Symbol are registered trademarks and tradenames of ITT Corporation.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

BCELEACC January, 2009

Copyright (c) 2009 ITT Corporation

Engineered for life