



## APPLICATIONS

Specially designed for the following uses:

- Basement draining
- Water transfer
- Dewatering

## SPECIFICATIONS

- Discharge size: 1" NPT.
- Capacities: to 1800 GPH.
- Maximum head: 10 feet TDH.
- Temperature: 104°F (40°C) maximum.
- Solids Handling: 1/16" maximum.
- Maximum Pump Down: 5/8" from base.

## DIMENSIONS

- Height: 7 3/4"
- Base Diameter: 4 7/8"
- Diameter at Discharge Elbow: 7"

## MOTOR

- Single phase, 115 V, 60 Hz.
- Stainless steel shaft.
- Air filled design.
- Power cord length: 8 feet.
- Energy efficient.
- DC permanent magnet motor. Consumes only 100 watts of power.
- 115 V, 60 Hz.

## FEATURES

- Corrosion-resistant construction.
- Stainless Steel motor shaft.
- Thermoplastic impeller and housing.
- Motor is permanently lubricated for extended service life and is powered for continuous operation. All ratings are within the working limits of the motor.

- Manual operation.
- Complete unit is lightweight and portable.
- Stainless steel inner screen.

## PERFORMANCE CHART

Head (ft.)	GPM	GPH	Discharge Hose Size
0	30	1800	1" NPT
5	21	1250	
10	12	700	